



TANGO 2

Safety Harness

STANDARD : CONFORMING TO EN 361:2002, IS 3521(Part 1): 2021  

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
-	Ladder climbing
-	Fall Arrest

SPECIAL FEATURES


 FALL ARREST	 RESTRAINT	 CLIMBING	 H-SHAPED	 CLASS-L	 CLASS-A
---	---	--	--	---	---

WEBBING MATERIAL	WEBBING WIDTH
Polyester	44 +/- 1 mm

WEBBING BREAKING STRENGTH
23 kN

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High tenacity virgin multifilament polyester	White

METAL COMPONENTS	HARNES COLOUR	WEIGHT
Shot Blasted Finish High Strength Steel with Zinc Plated thickness - Free of sharp edges. Capable of taking 50 hrs of neutral salt spray testing.	Blue and Green	1270 gms



TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 KN applied for 3 min.

TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mtr.



FEATURES

- One dorsal D-ring for fall arrest.
- Two Chest attachment D-rings
- Size adjustment straps at chest, shoulders and thighs
- Ergonomic horizontal H-shaped thigh straps
- No discomfort or pressure on the groin
- Improved comfort in case of a fall
- Built-in fall indicator for easy inspection

MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approval & IS marking
- Instruction Pictogram

STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct/ high heat or sunlight as this may distort the Colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

CLEANING

- Use Clean piece of cloth to wipe the dust

PACKING

- 10 pieces per carton