










UB103 Safety Harness

STANDARD : Conforming to EN 361:2002, IS 3521(Part 1) : 2021  

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Maintenance	Ladder climbing
-	Fall Arrest

SPECIAL FEATURES

 FALL ARREST	 RESTRAINT	 CLIMBING	 CLASS-L	 CLASS-A
--	--	---	--	--

WEBBING MATERIAL	WEBBING WIDTH
Polyester	44 +/- 1 mm

WEBBING BREAKING STRENGTH
23 kN

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High tenacity virgin multifilament polyester	White

METAL COMPONENTS	HARNESS COLOUR	WEIGHT
High quality alloy steel, zinc plated, free from any sharp edges.	Yellow & Black	1250 grams

TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 kN applied for 3 min.

TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mtr.





FEATURES

- One dorsal D-ring for fall arrest
- Two Sternal D-rings on chest
- Size adjustment straps only at shoulders, chest and thighs
- Ideally positioned sit-strap for extended comfort
- Built-in dual colour webbing for easy orientation

CLEANING

- Use Clean piece of cloth to wipe the dust

PACKING

- 10 pieces per carton

MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approval & IS marking
- Instruction Pictogram

STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct/ high heat or sunlight as this may distort the colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.