



ULTRATEK












Safety Harness

STANDARD : CONFORMING TO EN 361:2002,
EN 1497:2007, EN 813:2008, EN 358:2018, IS 3521:Part 1:2021



INDUSTRY	IDEAL APPLICATIONS
Construction	Rescue
Telecom	Rope Access
Transmission	Ladder Climbing
-	Work Positioning
-	Fall Arrest

SPECIAL FEATURES

					
FALL ARREST	RESTRAINT	CLIMBING	POSITIONING	LOWERING	
					
FRONT CLIMB	LOWERING IN SUSP. POS	CLASS-L	CLASS-A	CLASS-P	CLASS-D

WEBBING MATERIAL	WEBBING WIDTH
AZO free dyed synthetic Polyester	44 +/- 1 mm

WEBBING BREAKING STRENGTH
22kN (Min)

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High-tenacity virgin multifilament polyester	White

METAL COMPONENTS	HARNESS COLOUR	WEIGHT
High quality alloy steel, zinc plated, free from any sharp edges	Black	2200 grams

TEST COMPLIANCE - STATIC STRENGTH
Tested at each attachment element with a force of 15 KN applied for 3 min.



TEST COMPLIANCE - DYNAMIC STRENGTH
When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mt.



FEATURES		MARKINGS	
One dorsal D-ring for fall arrest		Manufacturers Logo, details & mailing address	
One sternal D-ring on chest for fall arrest		Address Model No., Batch No., Serial No.	
Two lateral D-rings on waist for work positioning		Year of Manufacture	
One Ventral D-ring at waist level for rope access		Material	
Comfortable and cushioned padding on Waist for comfort during long duration use		Approval & IS marking	
Y-shaped padding and Quick buckle on shoulder make it comfortable, simple, fast and easy access and donning		Instruction Pictogram	
Fully adjustable waist pad, thigh pads and back strap		STORAGE	
		Store the harness in a dry area away from ultraviolet rays.	
		Do not store in direct/ high heat or sunlight as this may distort the Colour.	
		Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.	
CLEANING		PACKING	
Use Clean piece of cloth to wipe the dust		5 pieces per carton	

