







UK01JKO
Safety Jacket Harness

STANDARD: EN 361 :2002, IS 3521 : (Part-1):2021  

| INDUSTRY | IDEAL APPLICATIONS | SPECIAL FEATURES | |
|--------------|--------------------|--|---|
| Construction | Working at Height |  FALL ARREST |  CLIMBING |
| - | Fall Arrest |  CLASS-A |  CLASS-L |
| - | Ladder Climbing | | |



| WEBBING MATERIAL | WEBBING BREAKING STRENGTH |
|------------------|---------------------------|
| Polyester | 25kN |

| WEBBING WIDTH | STITCH THREADS MATERIAL |
|---------------|--|
| 44 +/- 1 mm | High tenacity virgin multifilament polyester |

| JACKET COLOUR |
|--|
| Fluorescent Orange with reflective liner |

| METAL COMPONENTS | HARNESS COLOUR | WEIGHT |
|--|--------------------------------------|-----------|
| High Strength Steel with CED coated component for better durability. Free from sharp edges. Capable of taking 50 hrs of neutral salt spray testing | Orange & Black with reflective liner | 850 grams |

| TEST COMPLIANCE - STATIC STRENGTH |
|---|
| Tested at each attachment element with a force of 15 KN applied for 3 min |

| TEST COMPLIANCE - DYNAMIC STRENGTH |
|---|
| When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 meters |

Udyogi



| FEATURES |
|---|
| One dorsal D-ring for fall arrest |
| Two textile chest attachment loops |
| Size adjustment straps only at chest and thighs |
| Elasticated web keeper |
| Ideally positioned sit-strap for extended comfort |
| Ergonomic horizontal H-shaped harness |
| High strength abrasion resistant webbing |
| CED coated buckles for better durability |
| Lanyard parking attachments |
| Inspection label with QR scanning |
| Conforms to EN361:2002 & IS3521:2021 |
| Easy donning with zipper system |
| Special air-mesh fabric to enhance wearer comfort |
| Jacket with reflective strips for high visibility |

| MARKINGS |
|---|
| Manufacturers Logo, details & mailing address |
| Model No., Batch No., Serial No. |
| Year of Manufacture |
| Material |
| Approval CE & IS marking |

| STORAGE |
|--|
| Store the harness in a dry area away from ultraviolet rays |
| Do not store in direct/ high heat or sunlight as this may distort the colour |
| Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold |

| CLEANING |
|---|
| Use Clean piece of cloth to wipe the dust |

| PACKING |
|----------------------|
| 10 pieces per carton |

Udyogi