



UK01 Safety Harness

STANDARD: EN361:2002, IS 3521:(Part 1) : 2021  

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
-	Fall Arrest
-	Ladder Climbing

SPECIAL FEATURES			
			
FALL ARREST	CLIMBING	CLASS-A	CLASS-L

WEBBING MATERIAL	WEBBING WIDTH
Polyester	44 +/- 1 mm

WEBBING BREAKING STRENGTH
25kN

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High tenacity virgin multifilament polyester	White

METAL COMPONENTS	HARNESS COLOUR	WEIGHT
High Strength Steel with CED coated component for better durability. Free from sharp edges. Capable of taking 50 hrs of neutral salt spray testing.	Orange & Black with reflective liner	950 grams

TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 KN applied for 3 min.

TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mtr





FEATURES

- One dorsal D-ring for fall arrest
- Two textile chest attachment loops
- Size adjustment straps only at chest and thighs
- Elasticated web keeper
- Ideally positioned sit-strap for extended comfort
- Ergonomic horizontal H-shaped harness
- High strength abrasion resistant webbing
- CED coated buckles for better durability
- Lanyard parking attachments
- Inspection label with QR scanning
- Conforms to EN361:2002

MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approval & IS marking

STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct/ high heat or sunlight as this may distort the colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

CLEANING

- Use Clean piece of cloth to wipe the dust

PACKING

- 10 pieces per carton