



UK02
Safety Harness

STANDARD: EN 361:2002, IS 3521: (Part 1) : 2021  

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
-	Fall Arrest
-	Ladder Climbing

SPECIAL FEATURES



FALL ARREST



CLIMBING



CLASS-A



CLASS-L

WEBBING MATERIAL	WEBBING WIDTH
Polyester	44 +/- 1 mm

WEBBING BREAKING STRENGTH

25kN

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High tenacity virgin multifilament polyester	White

METAL COMPONENTS	HARNESS COLOUR	WEIGHT
High Strength Steel with CED coated component for better durability. Free from sharp edges. Capable of taking 50 hrs of neutral salt spray testing.	Orange & Black with reflective liner	980 grams



TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 KN applied for 3 min.

TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mtr

Udyogi



FEATURES
One dorsal D-ring for fall arrest
One chest attachment D-ring for fall arrest
Size adjustment straps only at chest and thighs
Elasticated web keeper
Ideally positioned sit-strap for extended comfort
Ergonomic horizontal H-shaped harness
High strength abrasion resistant webbing
CED coated buckles for better durability
Lanyard parking attachments
Inspection label with QR scanning
Conforms to EN361:2002

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approval & IS marking

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct/ high heat or sunlight as this may distort the colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

CLEANING
Use Clean piece of cloth to wipe the dust

PACKING
10 pieces per carton