



ULTRA01 Safety Harness

STANDARD : EN361:2002, EN358:2018, IS 3521(Part-1):2021  

INDUSTRY	IDEAL APPLICATIONS
Telecom	Working at Height
Tower	Fall Arrest
Transmission	Ladder Climbing
	Work Positioning

SPECIAL FEATURES



FALL ARREST



RESTRAINT



CLIMBING



POSITIONING



CLASS-A



CLASS-L



CLASS-P

WEBBING MATERIAL	WEBBING WIDTH
Polyester –abrasion resistant	44 +/- 1 mm

WEBBING BREAKING STRENGTH

25 kN

STITCH THREADS MATERIAL	STITCH THREADS COLOUR
High tenacity virgin multifilament polyester	White



METAL COMPONENTS	HARNESS COLOUR
High Strength Steel with CED coated component for better durability. Free from sharp edges. Capable of taking 50 hrs of neutral salt spray testing.	Orange & Blackstripes

TEST COMPLIANCE - Static Strength

Tested at each attachment element with a force of 15 kN applied for 3 min.

TEST COMPLIANCE - Dynamic Strength

When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 mtr.



FEATURES

- One dorsal D-ring for fall arrest.
- Two sternal D-rings on chest
- Two Lateral D-rings on waist for work positioning
- Absorption Resistant Webbing and Aluminium and alloy steel with quick connector
- Size adjustment straps only at Shoulders, chest, waist and thighs
- Ideally positioned sit-strap for extended comfort
- Built-in dual colour webbing for easy orientation
- Integrated work positioning memory foam padding.

MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approval & IS marking
- Inspection label

STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct/ high heat or sunlight as this may distort the colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

CLEANING

- Use Clean piece of cloth to wipe the dust

PACKING

- 10 pieces per carton