



**BL61**  
Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Construction	Work At Height
Process Unit	Fall Arrest



SPECIAL FEATURES	
 LIGHT WEIGHT	 FALL RESTRAINT

ROPE MATERIAL
10.5mm Kernmantle Rope

STITCHING THREAD
High Tenacity Virgin Multifilament Polyester

BREAKING STRENGTH	LANYARD LENGTH	SHOCK ABSORBER LENGTH
23 kN (Min)	1.8/2.0 meter (Hook to Hook)	0.3 m

MECHANICAL CHARACTERISTICS
Static strength of lanyard 22 kN (minimum)
Maximum dynamic load – 6 kN
Fall arrest distance – 5.75 m (Maximum)
Maximum capacity 100 kg (For the use of single user only)
Carabiner 313 gate opening – 18 mm (Maximum)
SH-61 hook gate opening – 55 mm (minimum)

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approval & IS marking
Instruction Pictogram

FEATURES
Energy Absorbing Double Braided Rope Lanyard
One side (Lanyard End) connected with SH-61 Aluminium scaffolding hook and on other side connected with quarter turn (EASY 313) Carabiner

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

PACKING
10 pieces per carton

CLEANING
Use clean piece of cloth to wipe the dust

**Udyogi**