



EDGE MINI BLOCK
Retractable Fall Arrester

STANDARD : CONFORMING TO EN 360:2002

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES
Construction	Working at Height	 FALL ARREST
Cement Plant	Loading / Unloading	
Steel Plant	EOT / Gantry walkway	AVAILABLE LENGTH 2.5 meter
Refinery	Tanker Inspection	
Chemical & Pharma	Maintenance at Vessel	



MECHANICAL CHARACTERISTICS	PHYSICAL PARAMETERS
Breaking Strength - 15 kN	Robust & durable casing made from high impact glass field nylon Fitted with inertia breaking system In-built shock absorber, snap hook and karabiner Snap hook equipped with fall indicator
Braking Force - Less than 6 kN	
Fall Arrest Distance - 1.5 m (Maximum)	
Temp. Range - -30°C to 50°C	

FEATURES
Webbing type retractable fall arrester
High Impact resistance polyamide casing
Webbing rope with swivel snap hook
In case a fall occurs, the automatic braking system in the block immediately arrests the
fall Maximum load capacity: 100 kg

STORAGE
Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

CLEANING	PACKING
Use clean piece of cloth to wipe the dust	4 pieces per carton

RETRACTABLE LANYARD
Material - Webbing
Width – 47 mm
Breaking Strength - Greater than 15 kN

TEST COMPLIANCE - STATIC STRENGTH
When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 m

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Approval & EN standard
Instruction Pictogram