



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS
Cement	Construction & projects works
Automotive	Material handling
Power & utilities	Shop floor
Metals & mining	Packaging
Iron & steel	Maintenance

SPECIAL FEATURES				
LIGHT WEIGHT	RECYCLABLE	STRONG & DURABLE	TEMPERATURE RESISTANT	RATCHET FIT

COLOURS: White

**Lighton M**  
A Mounting Safety Helmet

STANDARD : EN 12492:2012, EN 397:2012+A1:2012, CE

COMPONENT	MATERIAL	ADVANTAGES
Shell	ABS (Acrylonitrile Butadiene Styrene)	Resistant to high radiant heat
Peak	ABS	Peak less helmet for unobstructed vision
Brim	ABS	Rim around the shell, drains rain water
Foam & Pad	Foam/removable comfort pads	Prevents impact from front- rear- sides with sweat wicking washable pads
Head band	Plastic	Universal fit, dia. 52 cm – 63 cm
Sweat band	Soft pad	Non-contact sweat band maximizes comfort, long time use
Chin strap	Artificial leather/PP	'Y' type chinstrap, Holds the shell perfectly, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Ratchet	Nylon	Fully adjustable, smooth & universal fit
Slot	Universal slots on the both side	Compatible with head & face PPE accessories
Ventilation	Both side of the crown ventilated	4 point anti-intrusion grilled ventilation prevent debris, air circulates

FEATURES
Shell made of ABS compound
Pressure absorbent foam & soft pads with ratchet fit adjustment
Anti-intrusion grilled ventilation prevent debris while allows air circulation
High quality sweat band provides comfort
Use in industries where there is a hazard of falling from the height
Lower extension of nape strap to prevent dislodging
Excellent rain management system to effectively reduce the flow of water down the neck
Aesthetic, aerodynamic look with smooth finish – solid colour resin for a permanent, no-chip, no-peel finish
Tensile strength is higher than HDPE helmets, protects head from the all around impacts

APPLICATION
Best use for climbing, height work, confined space entry, facade cleaning, construction, general manufacturing, heavy infrastructure, industrial maintenance etc.
Can be used where ambient temperature is high

STORAGE
Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
Shell may be stored in the dark for up to 5 years
Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING	WEIGHT	PACKING
Clean using warm soapy water and soft cloth	490 grams	20 pieces per carton
Do not use solvents or abrasives		

**Udyogi**