



TECHNICAL DATA SHEET

LIGHTON M

Product Introduction:

- This lightweight design mountaineering safety helmet combines advanced safety and superior comfort, making it ideal for various demanding environments
- The ABS shell ensures outstanding impact resistance & durability, while also offering superior heat resistance to safeguard the wearer in high-temperature conditions & the cushion padded suspension provides extra comfort.
- Designed to meet EN12492:2012, EN397:2012+A1:2012,
 CE standard, it ensures maximum protection for the wearer in various high-risk environment.



Features:

- ABS provides excellent impact resistance, making these helmets effective in protecting against shocks & collisions.
- Anti-intrusion grilled ventilation prevent debris while allows air circulation
- Additional padding in the suspension system for increased comfort and protection
- Compatible with head & face PPE accessories
- 'Y' type chinstrap, Holds the shell perfectly, universal fit
- Excellent rain management system to effectively reduce the flow of water down the neck
- Tensile strength is higher than HDPE helmets, protects head from the all around impacts

Benefits:

- **Cost-Effective:** Choose proper helmets for proper application. The ABS material has excellent impact resistance, making it suitable for use in harsh environments.
- **Regulatory Compliance:** Assists in meeting safety and environmental regulations by providing protection against falling objects. This meets the standard for mountaineering equipment.
- Field of Vision: Designed to provide a wide field of vision, crucial for safety in dynamic environments.
- **Safety Improvement:** The textile suspension system with a ratchet fit mechanism allows for easy and precise adjustment, ensuring a secure and comfortable fit.
- Microbial Coating: Anti-microbial coatings on the cushioned suspension to prevent odor & bacterial growth
- **Durability:** ABS is resistant to many chemicals, including acids, alkalis, and oils, making it suitable for use in industrial environments where exposure to hazardous substances is possible.

Udyogi

E-mail: info@udyogi.net Website: www.udyogisafety.com Tel.: +91 33 2225 1470/71/72





Product Specifications:

Model: LIGHTON M

Construction: ABS (Acrylonitrile Butadiene Styrene)

Ventilation: Anti-intrusion grilled ventilation

Variants: Textile ratchet fit

Weight: : 490 grams

Color: : White, Navy blue

Accessories slot size: 30 mm.

Internal vertical clearance: 46 mm.

Wearing height: 80 mm.

Circumference of Headband: 520-630 mm.

Cradle width: 21 mm.

Chin strap width: 15 mm

Packaging: 20 pcs. per carton

Standard: EN397:2012



Applications:

- The ABS shell provides excellent protection against falling objects which ensures the wearer's safety in case of an accident. Best Used in industries where there is a hazard of falling from the height.
- ABS is resistant to many chemicals, including acids, alkalis, and oils, making it suitable for use in industrial environments where exposure to hazardous substances is possible.
- The helmet can withstand different weather conditions without degrading, ensuring consistent performance in diverse outdoor environments Ideal for high-altitude tasks.

Industry:

These helmets are utilized for their protective and practical features in various industries such as



d Marine











General Manufacturing

Steel

Automobile















Pharmaceutical

Chemical Agriculture

Transportation

FMCG

Udyogi

294, B. B. Ganguly Street, 2nd Floor, Kolkata - 700 012 E-mail: info@udyogi.net Website: www.udyogisafety.com Tel.: +91 33 2225 1470/71/72





Tel.: +91 33 2225 1470/71/72

Safety Information:

- When worn and maintained properly, safety helmets do a great job of protecting your head from a single impact.
- Excessive discoloration of the shell color of the surface may indicate a loss of strength. Such helmets should be discarded
- All components, shells, harnesses, headbands, and accessories should be visually inspected at least weekly.
- Helmets with sound shells but with damaged, excessively dirty, or defective harness components should be withdrawn from service and the complete harness and cradle replaced.

Usage Instructions:

- Place the helmet squarely on your head, ensuring it covers the top of your forehead and sits level.
- Turn the ratchet knob present at the back side until the helmet fits snugly and comfortably.
- Adjust the chin strap length to ensure a tight fit without causing discomfort.
- Turn the ratchet knob to the left and loosen the chin strap to put the helmet off.

Storage:

- Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
- Shell may be stored in the dark for up to 3 years
- Do not store in direct / high heat or sunlight as this may distort the suspension

E-mail: info@udyogi.net

Website: www.udyogisafety.com

Udyogi