



**VENTINOUT FL-60EX**  
Industrial Duct

**SPECIAL FEATURES**



COLOR	STYLE	TYPE
Black	Retractable	Flame Retardant

**VENTINOUT FL-60EX - FLEXIBLE ANTISTATIC DUCTING**

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

**CONSTRUCTION**

Vinyl and polyester anti-static materials
Single-Ply
Neoprene coated
Temperature range -65°F to 250°F (-53°C to 121°C)
Retractable, Non-collapsible design
Class 1 hard drawn spring steel wire helix
Black Colour with black weather-strip
Rated to 100,000 OHMS or less per square inch
Integrated with extended solid grounding wire at each end
Heat sealed seams for smoother surface for better air flow

**STORAGE**

Store in shadow, dry, room temperature
--

**CLEANING**

Store in shadow, dry, room temperature
--

**PACKING**

1 piece in a carton
---------------------



**FEATURES**

Quick and easy cinch belt securely fastens duct to blower housings and duct ends
Integral rigid duct end allows easy coupling of duct without the need for separate splicer accessory
Wire supported, non-collapsible
Close-pitched, wire-supported and features smooth interior walls for reduced flow restriction
Meet flame retardant material
Retractable for easier, safer storage
Diameter is 24" (600 mm)
Available lengths are 5/10/15 mtr.; duct can be coupled together for longer runs



**Udyogi**