





EDGE 15
Retractable Fall Arrestor

STANDARD : CONFORMING TO EN 360:2002 **CE** 0082

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Process plants	Ladder Climbing
Grinding Unit	Loading/Unloading point
Manufacturing Unit	Bag House and vessels maintenance

SPECIAL FEATURES	
 FALL ARREST	 STRONG



MECHANICAL CHARACTERISTICS
Breaking Strength - 15 kN
Breaking Force - Less than 6 kN
Fall Arrest Distance - 2 meter(Maximum)
Temp. Range - -30°C to 50°C

PHYSICAL PARAMETERS
Robust & durable casing made from high impact glass field nylon
Has a swivel anchorage eye at one end
Snap hook equipped with fall indicator and swivel function

RETRACTABLE LANYARD
Material - Galvanized Steel rope
Diameter - Φ 5.0 mm
Breaking Strength - Greater than 15 kN

TEST COMPLIANCE - DYNAMIC PERFORMANCE TEST
When subjected to a fall with a rigid mass of 140 kg., the breaking force is less than 6 kN, and the arrest distance is less than 2 meter

FEATURES
Wire rope type retractable fall arrester
High Impact resistance polyamide casing
Galvanized steel rope with swivel snap hook
In case a fall occurs, the automatic breaking system in the block immediately arrests the fall
Included nylon rope
Maximum load capacity : 140 kg

AVAILABLE LENGTH	AVAILABLE WEIGHT
15 meter	7kg

STORAGE
Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Instruction Pictogram

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
1 piece per box

Udyogi