



EDGE 3.5N
Retractable Fall Arrestor

STANDARD : CONFORMING TO EN360:2002

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Process plants	Ladder Climbing
Grinding Unit	Loading/Unloading point
Manufacturing Unit	Bag House and vessels maintenance

MECHANICAL CHARACTERISTICS

Webbing Material : UHMWPE Material (Ultra high molecular weight Poly Ethylene).
Min. Breaking Strength : 20 kN
Average force less than : 4 kN
Fall Arrest Distance : 42 inch (Max.)
Fall Arrest Force : 6 kN (Max.)
Safe Working Load : 140 kg
Free fall distance : 2 Inches (Max.)
Length : 3.3 m
Width : 19 mm
Weight : 1.45 kg



FEATURES

Has a Swivel Snap hook at one end and Swivel top to connect.
Extremely Compact, durable and light weight.
High capacity external shock absorber with impact indicator.
Quick-action breaking system.
High strength, anti-corrosion components.
Combination of an energy absorbing unit, with connector. Connector opening 18 mm.
Make of durable & light weight webbing material.

STORAGE

Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

MARKINGS

Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Instruction Pictogram

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

1 piece per box

Udyogi