




EDGE 6N
Retractable Fall Arrestor

STANDARD : CONFORMING TO EN 360:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height (Scaffolding Work)
Cement Plant	Loading / Unloading
Steel Plant	EOT / Gantry walkway
Refinery	Tanker Inspection

SPECIAL FEATURES		
 FALL ARREST	 STRONG	 LIGHT WEIGHT



MECHANICAL CHARACTERISTICS
Breaking Strength - 20 kN
Arrest force - Less than 6 kN
Fall Arrest Distance - 1.5 m (Maximum)
Temp. Range - -30°C to 50°C

PHYSICAL PARAMETERS
Robust & durable casing made from high impact Plastic ABS
Has an anchorage eye at one end with steel hook
Snap hook equipped with fall indicator

RETRACTABLE LANYARD
Material - Nylon Webbing Type
Width - 20 mm
Static Strength - Greater than 15 kN for 3 minutes

AVAILABLE LENGTH
6 meter

FEATURES
Webbing type retractable fall arrestor
Housing - High Impact resistance plastic ABS
Webbing with swivel snap hook (19 mm)
In case a fall occurs, the automatic breaking system in the block immediately arrests the fall
Maximum load capacity: 100 kg

TEST COMPLIANCE - DYNAMIC PERFORMANCE TEST
When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 m

STORAGE
Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Approvals & CE

PACKING
1 pieces per carton

CLEANING
Use clean piece of cloth to wipe the dust

Udyogi