







ANCHOR POST
Universal with Lifeline Support

STANDARD : EN 795 A,E:2012, TS 16415:2013, ANSI Z359.18:D:2017 **CE**

INDUSTRY	IDEAL APPLICATIONS
Construction	Temporary Horizontal Lifeline

SPECIAL FEATURES				
 LIGHT WEIGHT	 EASY TO CARRY	 ANCHOR POINT	 DURABLE	 FALL ARREST

MATERIAL AND CONSTRUCTION	
Structure	Steel
Welding Procedure	CSA W47,2M/CSA W59.1 & W47.1 & AWS D1.6
Surface Finishing Color	Yellow



WEIGHT	DIAMETER		HEIGHT
13.6 kg	Anchor Post (Inner Section)	ø79.40	1067 mm
	Anchor Post (Outer Section)	ø203.20	

LIFELINE SUPPORT FOR ANCHOR POST

MATERIAL AND CONSTRUCTION		WEIGHT	HEIGHT
Structure	Zinc Plated Steel GR5 & Stainless Steel	4.5 kg	268 mm

ANCHORAGE BREAKING STRENGTH		WORKING LOAD LIMIT	COMPONENTS
Anchorage 1 (Lifeline Support for Anchor Post)	22.2 kN	164 Kg	Adapter (Winch, Floor, Wall, Sleeve) Lifeline (LDV, HLL, HLL04) Mast
Anchorage 2 (for Anchoring)	29.3 kN		
Anchorage 3 (for Horizontal Lifeline)	29.3 kN		

Udyogi



SPECIFICATIONS
The universal post horizontal lifeline system designed for fall protection and retrieval
Its modularity makes it the perfect system for a variety of work environments
It can be temporarily or permanently installed on manmade or natural environments with adaptors
In either single or double post, the configuration, the universal post creates a safe work environment
When assembly is complete, accessories such as the self-retracting lifeline support (SRL) or winch, or a horizontal lifeline are ready to be attached with the universal post

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct/ high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

RESTRICTION
This equipment must be operated on a level surface
Ensure that all hardware and connecting pins are properly installed before used
In the occurrence of a fall or the safety of the equipment is in doubt, the equipment must be immediately removed from service and inspected by qualified person before reuse

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approval & IS marking
Inspection label

AFTER SALES SERVICES		
Inspection	Training	Support