





**BL80**  
Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 **CE**

INDUSTRY	IDEAL APPLICATIONS
Construction	Work At Height
Process Unit	Fall Arrest

SPECIAL FEATURES	
 LIGHT WEIGHT	 FALL RESTRAINT

ROPE MATERIAL
10.5mm Kernmantle Rope

STITCHING THREAD	SHOCK ABSORBER LENGTH
High Tenacity Virgin Multifilament Polyester	0.2 meter

FEATURES
Energy Absorbing Double Braided Rope Lanyard
One side is connected with two Tower Hooks and other side is connected with one EASY 308 Carabiner.
Gate opening of tower hook 85 mm (max.) and Gate opening of 308 carabiner is 17 mm (max.).

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.



BREAKING STRENGTH	LANYARD LENGTH
23kN (Min)	2 meter

TEST COMPLIANCE-DYNAMIC PERFORMANCE
The dynamic performance test shall be conducted as specified in with a rigid steel mass of 100 kg, raising the mass to its maximum height and without using an additional chain lanyard. The fall arrest force Fmax shall not exceed 6 kN , the arrest distance H shall not exceed 5.75 m.

TEST COMPLIANCE-STATIC STRENGTH
With a force of 15 kN, the fully developed energy absorber shall withstand the static strength test without tearing or rupture.

**Udyogi**



Scan Here For More Info

MARKINGS	
Manufacturers Logo, details & mailing address	
Model No., Batch No., Serial No.	
Year of Manufacture	
Material	
Approval & CE	
Instruction Pictogram	

CLEANING	PACKING
Use clean piece of cloth to wipe the dust	10 pieces per carton

**Udyogi**