

DPL NEOTHERM[®]

Thermal protection with
extra power of Kevlar[®]

The only neoprene
specially coated
Contact heat level
3/cut 5 glove in
the market

Applications

Casting/ Molding
Ceramic/Cement industries
Industrial/Domestic kitchens
Bakeries
Automotive repairing
Power and energy

Special Features

- EN 407:2004
 - 1 Resistant to Flammability - Level 4
 - 2 Contact Heat Resistance - Level 3
 - 3 Convective Heat Resistance - Level 3
 - 4 Radiant Heat Resistance - Level 2
 - 5 Resistance to Small Splashes of Molten Metal - Level 4
- Liquid proof Neoprene layer (reusable)
- Grip pattern in the outer layer
- Additional Features: level 5 cut resistance
- Kevlar[®] engineered fiber is 5 times stronger and provides excellent protection from cuts and abrasion hazards
- Kevlar[®] is flame resistance and can withstand heat up to 900°F (400°C) without degrading
- Highest protection against aqueous acids
- Excellent tactile properties



NeoTherm[®]

Industrial grade neoprene coated glove that offers unbeatable protection against chemical, mechanical and thermal hazards.

EN 388 properties (Internal)

Abrasion	3
Cut	5
Tear	4
Puncture	3

★ Patent Pending

DPL
Handling you with care

Dipped Products PLC

400, Deans Road,
Colombo 10, Sri Lanka
Phone: +94 11 268 3964
E-mail: marketing@dplgroup.com

PROTECTIVE HANDWEAR SOLUTIONS

www.dplgroup.com