




EDGE 20
Retractable Fall Arrester

STANDARD : CONFORMING TO EN360:2002

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES
Construction	Working at Height	 FALL ARREST
	Ladder Climbing	
	Fall Arrest	

MECHANICAL CHARACTERISTICS
Max Arresting Force - Less than 6 kN
Max Fall Arrest Distance - 1.4 m
Temp. Range - -30°C to 50°C

PHYSICAL PARAMETERS
Robust & durable casing made from high impact thermoplastic
Has a swivel anchorage eye at top
Snap hook equipped with fall indicator and swivel action

RETRACTABLE LANYARD
Material - Galvanized Steel
Diameter - Φ4.8 mm
Breaking Strength - Greater than 15 kN

TEST COMPLIANCE - STATIC STRENGTH
When subjected to a fall with a rigid mass of 140 kg., the breaking force is less than 6 kN, and the arrest distance is less than 1.4 m



FEATURES
Galvanized steel rope type retractable fall arrester with steel swivel snaphook
High Impact resistance thermoplastic housing
Has Internal Shock Absorbing System
In case a fall occurs, the automatic breaking system in the block immediately arrests the fall
Available with Conduit rope for better operation

LENGTH
20 meter

WEIGHT
8.8kgs

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Instruction Pictogram

STORAGE
Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
1 piece / carton

Udyogi