



# FR5G PRO

## Safety Gloves

**STANDARD :** EN 388, ANSI A4, EN487, CE  
4X43D CUT 4122XX Cat III  
Arc Rating(ATPV)= 10.3 cal/cm<sup>2</sup>  
Level 2 per ASTM F2675 / F2675M-19



INDUSTRY
Machinery and Equipment
Electric & Gas Utilities
Oil and gas
Automotive
Automotive

IDEAL APPLICATIONS
General handling
Heavy material handling
General manual jobs
Oil & grease jobs
Quality control

SPECIAL FEATURES				
OILY ENVIRONMENT	GRIP	ABRASION	CUT-RESISTANT	DEXTERITY

LINER TYPE	COATING	ADVANTAGE
Uhmwpe & Fr yarn	Neoprene / Nitrile	Flame, Heat, Arc Flash and cut resistance. The touchscreen compatible property ensures workers use mobile phones easily without taking off the gloves

LINER COLOUR	COATING COLOUR	COATING TYPE	SIZE	CUFF	CERTIFICATION
Yellow	Black	Palm Coating	9 250 mm length	Normal overlocked	EN 388, ANSI A4, EN487, CE 4X43D CUT 4122XX Cat III Arc Rating(ATPV)= 10.3 cal/cm <sup>2</sup> Level 2 per ASTM F2675 / F2675M-19

FEATURES
UHMWPE & FR composite yarn and thin 13g knitted liner, delivering EN ISO D /ANSI A4-level cut resistance and protecting hands by enabling safe sharp component handling
ARC FLASH TESTED: Arc- flash testing placed these gloves Arc Rating (ATPV) = 10.3 cal/ cm <sup>2</sup>
Microfoam finish palm coating gives these gloves an excellent grip and superior comfort
Excellent flexibility and dexterity minimizing hand fatigue Breathable back of the hand to keep hands cool while working
Multiple launderings while keeps very good performance

APPLICATION
Tasks with potential for arc-flash or flash-flame exposure
De-energized electrical equipment panels
Facility and machinery maintenance

STORAGE
Store in cool and dry place
Do not store in direct / high heat or sunlight
Can be stored and transported in their original cartons

LAUNDERABLE	PACKING
Yes	120 pairs per carton

**Udyogi**

294, B. B. Ganguly Street,  
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net  
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72