




EDGE HUMMER

STANDARD: IS: 15298-Part 2 5

LD GETTOTHILLIC	
Microfiber Safety Shoe	
STANDARD - IS - 15200 Dowt 1	

INDUSTRY	
Logistics & Transports	Hotel, Production Process
Automotive	Electronics

















COMPONENT	MATERIAL	ADVANTAGE
Upper	Suede Microfiber with Reflector	Excellent resistance to hydrolysis, abrasion etc.
Lining	Spacer with foam padded 200gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy Steel toe	Protective reinforcement in the toe which protects the foot from falling object
Sole	Double density Polyurethane (PU)	Antistatic,Resistance to slip and bending performance, DIP PU Cleated sole with Extended toe guard
Insocks	Perforated EVA	Improved shock absorption, prevent jerk, ankle & leg injuries. Extra comfortable work

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
	Nulsa Line Committee Commi	1050 gms for size-8 with			
Foam padded	Foam padded	Coated round	nd Nylon Nylo	Nylon 3/6 ply	tolerance of ± 5% for all sizes

FEATURES
Very good physical & chemical properties
High tear & tensile endurance
Excellent resistance to abrasion
Excellent breathability
Slip resistance sole-SRC
Durability
Ease of care
Antistatic PU Sole
Water resistance upper
Anti-bacterial & Odor free
Alloy Steel toe cap - 200 J impact resistance

ΔPI	PLIC	ΔΤΙ	ON
$\Delta \Gamma I$		\sim 11	\mathbf{v}

Transport: Automotive / Aerospace

IT & Technology - Telecom, Production Process

Oil & Gas, Construction

STORAGE

Store away from sunlight, at room temperature

Keep in a dry, well ventilated space

Keep in cleaned and ready to be used condition

PACKING	SIZE	CLEANING
10 pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Udyogi

294, B. B. Ganguly Street, 2nd Floor, Kolkata - 700 012 E-mail : info@udyogi.net Website : www.udyogisafety.com Tel.: +91 33 2225 1470/71/72