








UB 102 QB
Full Body Harness

STANDARD : EN 361: 2002, IS 3521(Part-1): 2021  

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Cement	Ladder Climbing
Pharma	Fall Arrest
Petrochemical	Loading-Unloading
Chemical	
Beverage	



SPECIAL FEATURES				
 FALL ARREST	 CLIMBING	 RESTRAINT	 CLASS-A	 CLASS-L

WEBBING WIDTH 44 +/- 1 mm	WEBBING BREAKING STRENGTH 23 kN(Min)	WEBBING MATERIAL Polyester
STITCH THREADS MATERIAL High tenacity virgin multifilament polyester		STITCH THREADS COLOUR White
METAL COMPONENTS High quality alloy steel, zinc plated & powder coated free from any sharp edges	HARNESS COLOUR Yellow & Black	WEIGHT 1 kg (approx.) Without lanyard

TEST COMPLIANCE - Static Strength Tested at each attachment element with a force of 15 KN applied for 3 min.	HARNESS COLOUR Yellow & Black
--	---

TEST COMPLIANCE - Dynamic Strength When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4m (EN), 1m (IS)
--

Udyogi



FEATURES	
One dorsal D-ring for fall arrest.	
Two textile chest attachment loop for fall arrest.	
Size adjustment straps only at chest and thighs	
Easy to put on & off with Quick Buckle during emergency	
Ideally positioned sit-strap for extended comfort	
Built-in dual colour webbing for easy orientation	
In built Fall Indicator to facilitate easy inspection in case a fall has occurred ever	
CLEANING	
Use Clean piece of cloth to wipe the dust	
PACKING	
10 pieces per cartoon	
MARKINGS	
Manufacturers Logo, details & mailing address	
Model No.	
Batch No. & Serial No.	
Year of Manufacture	
Approvals CE & IS marking	
Approval & IS marking	
Instruction Pictogram	
STORAGE	
Store the harness in a dry area away from ultraviolet rays.	
Do not store in direct/ high heat or sunlight as this may distort the colour.	
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.	