





**RW18**  
Winch

STANDARD : EN 1496 : 2017 TYPE A **CE**

INDUSTRY	IDEAL APPLICATIONS
Municipal Corporation	Anchorage & Rescue
Oil & Gas	
Pharmaceutical, Cement	Confined space entry

SPECIAL FEATURES	MECHANICAL CHARACTERISTICS
 ANCHOR  RESCUE	IS 2062 Steel, Golden zinc plating
	Tensile strength more than 12kN
	Safe working load limit 150 kg

MODEL	LENGTH	WEIGHT
RW18-10	10 meter	10.0 kg
RW18-20	20 meter	10.9 kg
RW18-30	30 meter	11.7 kg

FEATURES
To be used for raising or lowering of personnel into confined space
Should be used with Udyogi Tripod

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approvals & CE



PHYSICAL PARAMETERS
Rope Material : Stainless Steel
Wipe rope dia. : Ø5 mm
Wire construction : 7 X 19 C

STORAGE
Can be stored and transported in their original cartons to avoid wear & tear due to atmospheric moisture, excessive heat or coldt

PACKING
1 pc per carton

**Udyogi**