



EDGE-212
TRIPOD

STANDARD : EN795:2012 (TYPE B), CEN/TS 16415:2013

| INDUSTRY | IDEAL APPLICATIONS |
|----------------|----------------------------------|
| Utilities | Anchorage |
| Oil & Gas | |
| Pharmaceutical | Confined space vertical entry |

SPECIAL FEATURES



MECHANICAL CHARACTERISTICS

- Tripod Head: High strength IS 2062 steel, golden yellow powder coated
- Tripod Legs: High strength aluminium alloy
- Strength: 15 kN (Minimum)
- Safe working load limit: 150 kg
- Maximum user: 2 person

FEATURES

- With two mounted pulleys at the head of the Tripod in the extension of the main leg for passing a cable
- Having two attachment points and that can be used simultaneously
- Strength of anchorage point greater than 12 kN
- Steel support-shoes provided with rubber sole to increase friction and impart more stability
- Every Tripod is provided with Kit Bag
- Light Weight, Durable and Easy to carry and install

STORAGE

Should be stored and transported in their original kit bag/ cartons to avoid wear & tear due to atmospheric moisture, excessive heat or cold.



PHYSICAL PARAMETERS

- Maximum working height: 2100 mm
- Adjustable Height: From 1400 mm to 2100 mm
- Wheelbase Footprint Ø: 1000 mm to 1500 mm
- Weight: 16 kg

MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Approvals & CE

PACKING

1 pc per carton