



EDGE-212 TRIPOD

STANDARD : EN795:2012 (TYPE B)
CEN/TS 16415:2013

INDUSTRY	IDEAL APPLICATIONS
Municipal Corporation	Anchorage
Oil & Gas	Confined space vertical entry
Pharmaceutical	

SPECIAL FEATURES



ANCHOR

MECHANICAL CHARACTERISTICS

High strength steel and aluminium alloy

Strength: 15 kN (Minimum)

Safe working load limit: 150 kg

Maximum user: 2 person

FEATURES

With two mounted pulleys at the head of the Tripod in the extension of the main leg for passing a cable

Having two holes as attachment points and can be used simultaneously.

Tripod head : IS 2062 Steel, Golden yellow powder coated and Tripod leg: Aluminium

Steel support-shoes provided with rubber sole to increase friction and impart more stability

Strength of anchorage point greater than 12 kN

Every Tripod is provided with integrated fixture for attaching UDYOGI Winch

Every Tripod is provided with Kit Bag

Net Weight : 17.0 kg (approx.) without winch

Light Weight, Durable and Easy to carry and install



PHYSICAL PARAMETERS

Maximum working height : 2100 mm

Adjustable Height : From 1400 mm to 2100 mm

Wheelbase : 1000 mm to 1500 mm

MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Approvals & CE

STORAGE

Can be stored and transported in their original kit bag/ cartons to avoid wear & tear due to atmospheric moisture, excessive heat or cold.

PACKING

1 pc per carton

Udyogi