



EDGE NANO TWIN

Retractable Block with Scaffolding Hook and adaptor

STANDARD : EN360:2002

INDUSTRY	IDEAL APPLICATIONS
Construction	Working at Height
Process plants	Ladder Climbing
Grinding Unit	Roof maintenance
Manufacturing Unit	Bag House and vessels maintenance

SPECIAL FEATURES



FALL ARREST



STRONG



LIGHT WEIGHT



MECHANICAL CHARACTERISTICS

Webbing Material : UHMWPE Material (Ultra high molecular weight Poly Ethylene).
Min. Breaking Strength : 20kN
Average force less than : 6 kN
Fall Arrest Distance : 42 inch (Max.)
Safe Working Load : 140kg (Max.)
Length : 1.8 m
Weight : 3.55 kgs

FEATURES

Has Scaffolding hooks at both end.
Extremely Compact, durable and light weight.
High capacity external shock absorber with impact indicator.
Quick-action breaking system.
High strength anti corrosion components.
Combination of dual unit, with connector.
Make of durable & light weight webbing material.

MARKINGS

Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Instruction Pictogram

STORAGE

Store the retractable in a dry area away from ultraviolet rays
Can be stored and transported in their original carton to avoid corrosion due to atmospheric moisture, excessive heat or cold

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

1 piece per box

Udyogi