



WPL(B)

Work Positioning Lanyard
with Braided Rope

STANDARD : CONFORMING TO EN 358:2018 **CE**

| INDUSTRY | IDEAL APPLICATIONS | SPECIAL FEATURES |
|--------------|--------------------------|------------------|
| Wind | Work Positioning Lanyard | LIGHT WEIGHT |
| Telecom | | FALL RESTRAINT |
| Power | | WORK POSITIONING |
| Transmission | | |

MECHANICAL CHARACTERISTICS

Material – Polyamide braided

Rope dia – 14 mm

Minimum Rope Breaking Strength – 22 kN

The breaking tenacity of the synthetic fiber of rope sheath be at least – 0.6 N/ tex

Maximum length: 1.3mtr.

Maximum rated load: 100kgs

TEST COMPLIANCE - STATIC STRENGTH

After releasing the 1KN load for 5 times apply a 5 kN static force for 3 minutes, record the slippage shall not exceed 50 mm and apply another 15 kN static force for 3 minutes, the work positioning lanyard shall not be fractured.

TEST COMPLIANCE - DYNAMIC STRENGTH

The work positioning lanyard shall not allow the dummy to be released, when fitted to a 100 kgs rigid mass and released from 1 meter height.

FEATURES

Made up of Polyamide braided rope of dia 14 mm

On each end a thimble sewn loop protected by a polyethylene sleeve and easy to connect steel carabiners (EASY308) at both ends of the attachment, complying with the standard EN 362

Equipped with convenient adjustment from 1 meter to 1.3 meter adjuster for easy length adjustment



MARKINGS

Manufacturers Logo

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approval & marking

Instruction Pictogram

STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

CLEANING

Use Clean piece of cloth to wipe the dust

PACKING

10 pieces per carton