



## HEAT-X (HX572LG12) Fire Proximity Leg-guard

FABRIC CERTIFICATION : EN ISO 11612:2015

INDUSTRY		MODEL DESCRIPTION
Metal	Oil & Gas	Velcro adjustment
Mining	Cement	Universal size
Automotive	Heavy Engineering	Hidden steel plate for better fitting (optional)
Power Distribution	Construction	

**HEATX**™

Outer Shell  
EN ISO 11612:2015



A1 B1 C3 D3 E3 F1

Inner Shell  
EN ISO 11612:2015



A1 B1 C1 F1



### SPECIAL FEATURES



IFR



LIGHT WEIGHT



FLEXIBLE




DURABLE

STYLE	FABRIC COMPOSITION	TRIM	MARKING
Leg-guard	Outer shell: 100% Aluminized Para-aramid (480g/m <sup>2</sup> ±5%) Inner shell: 100% Treated FR Cotton 240 g/m <sup>2</sup>	<ul style="list-style-type: none"> <li>• 100% Para-aramid Thread</li> <li>• FR Velcro</li> </ul>	Manufacturer Logo, Model No., Fabric Composition, Certification, Size

FEATURES	APPLICATIONS
Skin friendly fabric	Metal Foundries & smelting operations
Protection against molten metal	Pot Room & Blast Furnace
Protection against high radiation heat	Casting, Forging & heat treating
FR performance will remain same during the working life	Metal Fabrication & Foundry Equipment Maintenance
The hi-tech fabric will not cause any itchiness, stiffness	Energy & Utilities

STORAGE
May be stored in the dark for upto 2 years
Do not store in direct/high heat or sunlight at this may distort the properties of the fabric
Can be stored and transported in their original cartons at ambient temperature

FABRIC COMPOSITION
 <ul style="list-style-type: none"> <li>Inner Shell- 100% Treated FR Cotton 240 g/m<sup>2</sup></li> <li>100% Para-aramid Thread</li> <li>Outer Shell- Aluminized Para-aramid 480 g/m<sup>2</sup></li> </ul>

### Udyogi



Scan Here For More Info

COLOUR	SIZE	CLEANING	PACKING
Silver	12 Inch	Cleaned dry with a soft brush.	1 pair per packet

#### EN ISO 11612:2015 - OUTER SHELL

CODE	INSPECTION CHARACTERISTIC	STANDARD	LEVELS
A	Limited Flame spread	ISO 15025	1 ( Lowest 1, Highest 3)
B	Convective Heat	ISO 9151	1 ( Lowest 1, Highest 3)
C	Radiant Heat	ISO 6942	3 ( Lowest 1, Highest 4)
D	Liquid Molten Aluminium	ISO 9185	3 ( Lowest 1, Highest 3)
E	Liquid Molten Iron	ISO 9185	3 ( Lowest 1, Highest 3)
F	Contact Heat	ISO 12127	1 ( Lowest 1, Highest 3)

#### EN ISO 11612:2015 - INNER SHELL

CODE	INSPECTION CHARACTERISTIC	STANDARD	LEVELS
A	Limited Flame spread	ISO 15025	1 ( Lowest 1, Highest 3)
B	Convective Heat	ISO 9151	1 ( Lowest 1, Highest 3)
C	Radiant Heat	ISO 6942	1 ( Lowest 1, Highest 4)
F	Contact Heat	ISO 12127	1 ( Lowest 1, Highest 3)

#### CARE AND MAINTENANCE

- Chlorine bleach should never be used, this can change in the properties for which the manufacturer can assume no liability.
- Store the Aluminized leg-guard by hanging dry in a well ventilated area out of direct sunlight.
- Leg-guard for protection of close approach towards molten metals only.
- The life of leg-guard depends on use & exposure.
- Rubbing against rough or sharp edges is particularly harmful to the outer layer.
- Rough handling, folding and abrasion should be avoided.